

EXPRESS MAIL LABEL NO:
EL579666936US

METHOD, SYSTEM AND USER INTERFACE FOR INPUTTING AND
MANIPULATING TOKENISED STRINGS

Matthias Breuer

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to computer
generated documents and in particular to computer
generated index documents.

Description of Related Art

For many documents created on a computer, like text
documents, HTML documents, presentations and others,
related index pages are useful in finding desired content
within the document, or are useful in getting information
about bibliographic sources or the like. Index documents
include documents that in turn include any or all of a
table of contents, a headword index, figure or table
index as well as a bibliographic index, for example,
which are referred to herein as an index page.

Creating an index page involves a lot of formatting
work, and is therefore time consuming and costly. An
index page typically has a plurality of index lines
having a specific content and format. In an index page
that is a table of contents of a book, for example, there
exist index lines for different hierarchical levels of
headings, i.e., main heading, sub-heading etc.

Figure 1 shows an example of an index page 100 that
is a table of contents of a textbook. Index page 100 has

a plurality of index lines, which have different functions and are formatted differently.

The first index line is the title "Contents" followed by the index line "Summary" with page number 5.

5... Next are three index lines representing hierarchies of headings. A table of contents like that shown in Figure 1 is an example of an index page, where the index lines represent a different level in a hierarchical order within the index page.

10 Another example is a bibliographic index, which can contain a plurality of different types of information sources like books, journals, theses, e-mails, www-pages and so on. Different types of index lines, in this example, do not represent different hierarchical levels,
15 but do represent different types of information sources.

It is known to define the content and format of an index line using a string of instruction symbols (tokens) and attributes associated with the tokens. In the following an example of a token string with corresponding
20 attributes (in parenthesis) is provided for an index line of a table of contents, such as that in Figure 1:

chapter number **CH** (character style); entry text **ET**
(style template); tabulator **TAB** (type, filling
25 character, position); page number **PN** (character style).

Typically, "chapter number" is represented by a numerical value, e.g., 1, 1.1, 1.3.5. "Entry text" is
30 the chapter title and has a style defined by the style template. The tabulator filling character, e.g., a blank character or a dot, fills the space from the entry text to the page number. The tabulator has two other
35 attributes, i.e., the tabulator type (centred, left, right) and a position measured in mm, inches or any other suitable metric. In most cases, the page number is positioned at the right side of the index line.

09728556 "113000

It is known to either input the token string directly by typing the instruction symbols and attribute values, or by using a user interactive menu dialog. These two methods are complicated and time consuming for the user. Furthermore, the problem arises that the syntax of tokens and attributes may be input incorrectly.

Arranging the tokens to define an order is particularly difficult to handle because tokens could be entered inside another token. Therefore, the computer program has to check the syntax of the input token string every time, and if the syntax is wrong, the token string has to be corrected by the user. Besides index pages other instruction sets, for example defining a modem interface, may have to be input into a computer with correct syntax.

SUMMARY OF THE INVENTION

According to the present invention, a method of interactively generating a computer readable instruction set having instruction symbols and related variables comprises:

- a) generating a signal for displaying a list of selectable instruction symbols,
- b) arranging a selected instruction symbol to form part of the instruction set,
- c) generating a signal for displaying a list of selectable variable values, if at least one variable relates to the selected instruction symbol,
- d) arranging a selected variable value to form part of the instruction set, and
- e) repeating steps a) to d) until the instruction set is completed.

The instruction set may preferably define a formatted index document or database relating to another arbitrary document type.

In another embodiment, a computer-based method of interactively generating an index page displays a window

09728555 143000

including a list of index page types. Upon selection of one index page type in the list of index page types, a window including a list of index line types is displayed.

Upon selection of one index line type in the list of index line types, a token string including a plurality of tokens is displayed. The plurality of tokens includes only tokens appropriate for the one index line. Upon selection of one token, or alternatively a window for entering content associated with the one token, user selectable attributes for the content associated with the at least one token are displayed.

In one embodiment, index line types in the list of index line types represent different levels in a hierarchical order within the index page, and the list of index page types includes a table of contents. The list of index page types also includes a bibliographic index, and upon selection of the bibliographic index, the index line types in the list of index line types represent different sources of bibliographic information.

In one embodiment, the method of this invention is implemented using a computer-based graphic user interface comprising:

an insert index page dialogue window comprising:

an index page type window wherein the index page type window includes a list of index page types; and the index page type window displays at least one index page type in the list of index page types;

an index page title window coupled to the index page type wherein the index page title window displays a title for the at least one index page type;

an index line type window coupled to the index page type window wherein the index line type window includes a list of index line

5 displaying, for at least one token in the
 plurality of tokens, user selectable attributes
 for data associated with the at least one
 token.

In more general terms, one embodiment of the invention includes a user interface for inputting and manipulating tokenised strings such as those found on an index page. Furthermore, with this user interface, syntax errors in such strings can effectively be avoided.

Figure 1 is an illustrative example of a prior art index page.

20 Figure 3 is a schematic illustration showing an
exemplary dialog window displayed on a display screen
according to an embodiment of the present invention.

Figure 4 is a schematic illustration of a dialog window displayed on a display screen according to another
25 embodiment of the present invention.

Figure 5 is a flow chart schematically illustrating an embodiment of the present invention.

In the drawings and in the following detailed description, elements with the same reference numeral are the same element. Also, the first digit of a reference numeral represents the number of the figure in which that element first appeared.

35 A method 230 (Figs. 2 and 5), according to the
present invention, allows a user to easily and
conveniently generate each index line on an index page

using a single user interface 295 that is displayed on
monitor 216 of a computer system 200. Not only does each
index line generated using interface 295 have a correct
syntax, but also, the user is not required to use
5 multiple different interfaces, e.g., a first interface to
generate the index line and a second interface to edit
portions of the index line.

Herein, an index page comprises a plurality of index
lines, which have different functions and are formatted
10 differently. An index page may include one or more
physical pages of a document.

Although, the phrase "index line" is used here, an
index line is not limited to a single line on the index
page. In the sense of the present embodiment, an index
15 line can actually comprise two or more physical lines of
text that form a paragraph.

Formatting using graphic user interface 295,
however, is carried out for every index line. An index
line is therefore to be understood as a formatting unit.
20 In most cases, like the example shown in Figure 1,
however, every index line is actually one text line.

As explained more completely below, user
interface 295 of this invention includes all controls
necessary for a user to easily generate each index line
25 in an index page. Moreover, for each index line, the
user is presented with a framework that is correct with
respect to the hierarchical location of the index line
within the index page, or with respect to the type of
index line within the index page. In particular, upon
30 selection of a particular type of index line, the user is
presented only with tokens and data entry fields that are
appropriate for the chosen type of index line.

No longer does the user have to worry about improper
nesting of tokens used in formatting the various elements
35 in an index line. In fact, unlike the prior art
described above, no prior knowledge of the tokens or of
attributes of the tokens is required, because the correct

09728556-113000

tokens, preferably in the correct locations, are presented in interface 295 for each element in the index line level selected by this user. In addition, if there are style or other attributes associated with a particular token, the user accesses these attributes from interface 295 and makes the desired selections. The user is unconcerned with encoding the order or format used to specify the attributes of a particular token.

Figure 3 is a more detailed diagram of one embodiment of graphic user interface 295. As discussed more completely below, graphic user interface 295 includes an index page dialogue window that in this embodiment includes a plurality of windows that are used to select and generate each index line in the index page. Various buttons are used to expand some of the windows in interface 295. In another embodiment, index page dialogue window 295 includes a plurality of overlain cards that each has a tab. When the user selects a particular tab, that card is moved to the front of window 295. The particular technique used to implement the features of interface 295 of this invention are not essential to the invention, and will vary depending upon the characteristics of the computer system in which the invention is used, and the methods used to implement the invention in that computer system.

In one embodiment, to generate index page dialogue window 295, the user first accesses an Insert icon in a tool bar of an application in which the user wants to create the index page. Upon accessing the Insert icon, the user is presented with a menu that includes an entry "Indexes." Upon selection of entry "Indexes," the user is presented with yet another menu that includes "Indexes," that the user in turn selects. In response to this last selection, the user is presented with one embodiment of graphic user interface 295, as illustrated in Figure 3.

09728556 113000

In this embodiment of graphic user interface 295, the user can select a type of the index page of interest to the user using index page type window 301. In this embodiment, the index page type choices include:

5

Table of Contents
Alphabetic Index
Illustration Index
Index of Tables
10 User-Defined
Table of Objects
Bibliography.

09728556 "13000
The user selects a particular type of index page by clicking on button 308 and then selecting one type of index page from a list of index page types. Upon selection of the particular type of index page from this list, e.g., "Table of Contents" in Figure 3, a default title for that index page is entered in index page title window 302. However, the user can replace the default title, by selecting title window 302 and inputting a new title. Figure 4 is another embodiment of graphic user interface 295B in which the user selected an index page type of "Bibliography" in index page type window 301, and so the default title in title window 302 is "Bibliography".

Hence, in method 230 of this invention, display list of index page types operation 501 (Fig. 5) presents a list of index page types to the user upon activating button 308 in index page type window 301 of graphic user interface 295. From the list displayed in operation 501, a user selects one index page type from the list, e.g., "Table of Contents" in Figure 3, and "Bibliography" in Figure 4, in select index page type operation 502.

35 Upon the user selecting a particular index page type from the list in operation 502, graphic user interface 295 presents a list of index line types

page. However, in a given index line type, the string of tokens includes only tokens that are appropriate for elements in that type of index line type, e.g., tokens that represent each element in that type of index line type.

By clicking on the respective display field window on the screen the user can then enter the corresponding content, e.g., "1.1.2" in window 311A for chapter token 310A, or "fluids" in window 313A for title token 313A, in insert content operation 506. In one embodiment, not only is the content displayed in the window for the token, but also the entire index line is displayed in index page display window 325.

Typically, each token has a default style for the information entered in the display field window for that token. However, in addition, upon selecting a token, display selectable attributes operation 507 displays attributes that the user can define or modify for the selected token.

For example, in one embodiment, for token ET (Fig. 3), the user could select, in select attributes operation 508, either template 1 or template 2 to define the attributes of the text entered. In another embodiment, the user can use style window 304A to select a paragraph style associated with the index line represented by token string 303A in select attributes operation 508. If the user selected token TAB, the user can utilize tab window 305A to select the tab stop position and the fill character inserted between the title and the page number in select attributes operation 508. Hence, in this embodiment, the attributes may include style templates, character styles selected in character style window 307A or 307B, or tabulator positions.

When a user selects either a particular token or a display field window for that token, only the attributes associated with the specific selection are enabled in

09728556 113000

Therefore, the user can easily select appropriate attributes for the element in the index line associated with the token.

10 Similarly, the fields for inserting characters are only enabled if a character at the respective position is allowed.

Upon entering data for the selected token in operation 506 and selecting any attributes for the selected token in operation 508, all tokens check operation 509 determines whether the user has processed all the tokens in token string 303A. If all tokens have been processed, check operation 509 transfers to last index line check operation 510 and otherwise returns to select token and insert content operation 506. If the user has completed the index page, check operation 510 transfers to end and otherwise to select index line type operation 504.

While check operations 509 and 510 are presented as sequential operations in Figure 5, this is illustrative only and is not intended to limit the invention to this particular sequence of operations. As is known to those of skill in the art, an event handler is associated with a graphic user interface, and when an event occurs, the event handler determines what instruction the user has input, and branches to the appropriate action for that instruction.

Returning to Figure 4, where index line type book was chosen, token string 303B include tokens TIT (title) 310B, AUT (author) 312B, YEA (year) 314B and ED (editor) 316B that are displayed in operation 505 upon selection of index line type book in operation 504. The

09728556 " 113000

user can now input title, author, year of publication, editor etc in operations 506 to 508. Displayed tokens 310B, 312B, 314B, and 316B are adapted to the chosen document type so that all necessary information can be input. In the case of a web page, for example, it is possible to insert tokens for a hyperlink to the referenced www-page. Also, notice that since token string 303B does not include a tabulator token, tabulator window 305B is greyed-out to indicate that this attribute is unavailable.

The index page may be assigned to a document presently opened in the computer or a defined portion thereof as, for example, a chapter or paragraph. The invention, however, is not restricted to the generation of index pages. Other types of instruction sets may also be created by the present invention. An example of such an instruction set is an instruction string containing AT-commands for a modem interface.

The interactive editing of the instruction set speeds up the generation or editing of the instruction set. In the case of a bibliographic index, for example, the user may enter a short name for a field like the author. If a corresponding entry does not exist in the bibliographic index, the user can then click on a button to create a new entry for the bibliography. The interactive entry of instruction symbols and variables furthermore can avoid the entry of instruction language that is not permitted. As a user builds or edits an index page, in one embodiment, the index page is displayed in index page display window 325.

In one embodiment, graphic user interface 295 is implemented using a hardware configuration like a personal computer or workstation as illustrated schematically in Figure 2 by computer system 200. However, in another embodiment, graphic user interface 295 is implemented using a client-server configuration 250 that also is illustrated in Figure 2.

Graphic user interface 295 may be displayed on a display screen of client device 200 while some or all operations of method 230 are carried out on a server computer 280 accessible by the client device 200 over a data network 203 and 204, such as the Internet, using a browser application or the like.

Herein, a computer program product comprises a medium configured to store or transport computer readable code for method 230 or in which computer readable code for method 230 is stored. Some examples of computer program products are CD-ROM discs, ROM cards, floppy discs, magnetic tapes, computer hard drives, servers on a network and signals transmitted over a network representing computer readable program code.

As illustrated in Figure 2, this storage medium may belong to computer system 200 itself. However, the storage medium also may be removed from computer system 200. For example, method 230 may be stored in memory 284 that is physically located in a location different from processor 201. The only requirement is that processor 201 is coupled to the memory containing method 230. This could be accomplished in a client-server system 250, e.g., system 200 is the client and system 280 is the server, or alternatively via a connection to another computer via modems and analog lines, or digital interfaces and a digital carrier line.

For example, memory 284 could be in a World Wide Web portal, while display unit 216 and processor 201 are in a personal digital assistant (PDA), or a wireless telephone, for example. Conversely, the display unit and at least one of the input devices could be in a client computer, a wireless telephone, or a PDA, while the memory and processor are part of a server computer on a wide area network, a local area network, or the Internet.

More specifically, computer system 200, in one embodiment, can be a portable computer, a workstation, a two-way pager, a cellular telephone, a digital wireless

09728556 "113000

telephone, a personal digital assistant, a server
computer, an Internet appliance, or any other device that
includes the components shown and that can execute
method 230. Similarly, in another embodiment, computer
5 system 200 can be comprised of multiple different
computers, wireless devices, cellular telephones, digital
telephones, two-way pagers, or personal digital
assistants, server computers, or any desired combination
of these devices that are interconnected to perform
10 method 230 as described herein.

Herein, a computer memory refers to a volatile
memory, a non-volatile memory, or a combination of the
two in any one of these devices. Similarly, a computer
input unit and a display unit refer to the features
15 providing the required functionality to input the
information described herein, and to display the
information described herein, respectively, in any one of
the aforementioned or equivalent devices.

In view of this disclosure, method 230 can be
20 implemented in a wide variety of computer system
configurations. In addition, method 230 could be stored
as different modules in memories of different devices.
For example, method 230 could initially be stored in a
server computer 280, and then as necessary, a module of
25 method 230 could be transferred to a client device 200
and executed on client device 200. Consequently, part of
method 230 would be executed on the server processor 282,
and another part of method 230 would be executed on
processor 201 of client device 200. In view of this
30 disclosure, those of skill in the art can implement the
invention of a wide variety of physical hardware
configurations using an operating system and computer
programming language of interest to the user. For
example, Figure 2 shows input devices 215 and 218, but
35 other input devices, such as speech recognition software
and/or hardware could be used to input the selections and
data for method 230.

09728556 113000

In yet another embodiment, method 230 is stored in memory 284 of system 280. Stored method 230 is transferred, over network 204 to memory 211 in system 200. In this embodiment, network interface 283 and I/O interface 202 would include analog modems, digital modems, or a network interface card. If modems are used, network 204 includes a communications network, and method 230 is downloaded via the communications network.

Method 230 of the present invention may be implemented in a computer program including comprehensive office application STAROFFICE that is available from Sun Microsystems, Inc. of Palo Alto, CA. (STAROFFICE is a trademark of Sun Microsystems.) Such a computer program may be stored on any common data carrier like, for example, a floppy disk or a compact disc (CD), as well as on any common computer system's storage facilities like hard disks. Therefore, another embodiment of the present invention also relates to a data carrier for storing a computer program for carrying out the inventive method. Yet another embodiment of the present invention also relates to a method for using a computer system for carrying out the presented inventive method. Still another embodiment of the present invention further relates to a computer system with a storage medium on which a computer program for carrying out the presented inventive method is stored.

While the invention has been particularly shown with reference to a preferred embodiment thereof, it will be understood by those skilled in the art that various other changes in the form and details may be made therein without departing from the spirit and scope of the invention.

09728556 113000